

LandStar series

LS1024S/LS1524S/LS2024S

Application:

Surface mounting solar home System

Load work mode: manual ON/OFF

All the terminals backwards

LED indicator shows battery level, intuitive and convenient

- Intelligent System Optimum Control
- High efficient Series PWM charging with temperature compensation
- Compact size
- Use MOSFET as electronic switch, without any mechanical switch
- Digital LED menu, only one key choose the battery type
- Load status display
- Gel, Sealed and Flooded battery type option
- Big terminals and big distance between terminals (10A/6 mm², 15A, 20A/10 mm²)
-
- Reverse polarity protection: Any combination of solar module and battery

Model	LS1024S	LS1524S	LS2024S
Rated Current	10A	15A	20A
System Voltage	12/24V auto work		
Over Load Protection	1.25 times of rated current for 60 seconds, or 1.5 times for 5 seconds		
Short Circuit Protection	3.5 times of rated current		
Self- consumption	Max.6mA		
Working Temperature	-35°C to +55°C industrial		
Equalize Charging Voltage	14.6V;x2/24V		
Boost Charging Voltage	14.4V;x2/24V		
Float Charging Voltage	13.8V;x2/24V		
Boost Reconnect Charging Voltage	13.2V;x2/24V		
Temperature Compensation	-30mV/°C/12V		
Under Voltage Warning Voltage	12.0V;x2/24V		
Low Voltage Disconnect Voltage	11.1V;x2/24V		
Low Voltage Reconnect Voltage	12.6V;x2/24V		
Terminals	6 mm ²	10 mm ²	10mm ²
Enclosure	IP30		

Technical data for lead acid battery at 25°C

Product details

